

## Changsha YiGuang Pharmaceutical Machinery Co.,Ltd

Address: 2/F, Building A1, Lugu International Industrial Area, Yuelu District, Changsha, Hunan, China Tel:86-731-85634411 Fax:86-731-85634411 Email:felicia@csygyj.com www.csyhyj.com

# BY-300 sugar coating machine

#### Picture:



Attn:Felicia Mobile:+86-15013509826 Skype:felicia@csygyj.com Wechat:tracyliu123456 Title:Sales Manager Email:felicia@csygyj.com Whatspp/Viber:+86-15013509826



Changsha YiGuang Pharmaceutical Machinery Co.,Ltd

Address: 2/F, Building A1, Lugu International Industrial Area, Yuelu District, Changsha, Hunan, China Tel:86-731-85634411 Fax:86-731-85634411 Email:felicia@csygyj.com www.csyhyj.com

**Applications:** 

BY-300 sugar coating machine is suitable for the small batch

production and polishing of Chinese and Western tablets, pills, pellets,

pellets, water pills, drip pills, etc. in the pharmaceutical, food, chemical

and other industries. It is also suitable for spherical rolling in the

pharmaceutical, food and chemical industries. Powder mixed.

**Cautions:** 

In order to make the chip evenly coat and crystallize on its surface

layer as soon as possible, and to achieve the purpose of polishing, the

chip in the pot must be sprayed with sugar paddles by hand, and the

sugar-coated tablet is rolled in the pot by rotating the pot clockwise,

sliding friction grinding, so that it is evenly distributed on the tablets at all

the cores, while passing hot air into the pot to remove the water on the

surface of the tablet, and finally obtain a qualified sugar-coated tablet.

This machine is to provide the best pot body for this sugar coating



### Changsha YiGuang Pharmaceutical Machinery Co.,Ltd

**Title:Sales Manager** 

Email:felicia@csygyj.com

Whatspp/Viber:+86-15013509826

Address: 2/F, Building A1, Lugu International Industrial Area, Yuelu District, Changsha, Hunan, China Tel:86-731-85634411 Fax:86-731-85634411 Email:felicia@csygyj.com www.csyhyj.com

process, to ensure the tablet to form the best logistics curve in the pot at a stable line speed, to meet the process requirements of uniform thickness of the sugar coating layer, bright color and no pitting.

#### **Technical Parameter:**

1. Sugar-coated pot diameter: 300mm;

2. Production capacity: 1.5-3kg / time;

3.Inclination: 15° -45° adjustable;

4. Sugar-coated pan speed: 0-46 r/min;

5. Power: 1020w;

6. Equipment weight: 30kg;

7. Air volume of blower: 0.5m3 / min;

8. Equipment volume:  $550 \times 400 \times 930$  mm;